



SAFETY DATA SHEET

SDS FORM A: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS

The following Safety Data Sheet (SDS) is being provided pursuant to requirements of the Fed/OSHA (29 CFR 1910.1200) and Cal/OSHA (8 CCR 5194) Hazard Communication Standards. The health and hazards information given here is based on data believed to be accurate by Dunn-Edwards Corporation; we do not, however, assume any liability for the accuracy or completeness of this information. We neither suggest nor guarantee that any hazards mentioned are the only ones that may exist. All persons intending to rely on any recommendation, or to use any technique, equipment, or material mentioned should first satisfy themselves that they can meet all applicable safety and health standards.

The following SDS supersedes any previously issued SDS for each product covered. The reader is advised to destroy any obsolete SDS and refer only to this SDS. As permitted by OSHA, each SDS may apply to a class of products which have similar hazards and contents.

Products covered by this SDS are listed below:

ACBL10-1: ACRI-BUILD Flat	EVER50-0: EVEREST Semi-Gloss
ACHS10-0, -1: ACRI-HUES Flat	EVSH10-3: EVERSIELD Flat
ACHS30-0, -1: ACRI-HUES Eggshell	EVSH20-3: EVERSIELD Velvet
ACHS50-0, -1: ACRI-HUES Semi-Gloss	EVSH30-3: EVERSIELD Eggshell
ACWL10-1, -2: ACRI-WALL Flat Ready-To-Use	EVSH40-3: EVERSIELD Low-Sheen
ACWL30-1, -2: ACRI-WALL Eggshell	EVSH50-3: EVERSIELD Semi-Gloss
ACWL50-1, -2: ACRI-WALL Semi-Gloss	EVSH60-3: EVERSIELD Gloss
AQUA10-1: AQUAFALL Flat	EXQT10-0: EXQUISITE Matte
AQUA30-1: AQUAFALL Eggshell	EXQT30-0: EXQUISITE Eggshell
AQUA50-1: AQUAFALL Semi-Gloss	EXQT50-0: EXQUISITE Semi-Gloss
ASHL30-0: ARISTOSHIELD Eggshell	EZPR00-1: EZ-PRIME Premium
ASHL40-0: ARISTOSHIELD Satin/Low Sheen	EZSL00-0: EZ-PRIME Select
ASHL50-0: ARISTOSHIELD Semi-Gloss	FPSL00-1: FLEX-PRIME Select
ASHL70-0: ARISTOSHIELD High Gloss	PC3510-0: PRO-COM 3500 Flat
BIPR00-1: BLOCK-IT Premium	PC3530-0: PRO-COM 3500 Eggshell
BRPR00-2-RO: BLOC-RUST Premium, Red Oxide	PC3550-0: PRO-COM 3500 Semi-Gloss
BRPR00-2-WH: BLOC-RUST Premium, White	PC6510-0: PRO-COM 6500 Flat
CEIL10-0-LW8: CEILING PAINT Dead Flat	PC6540-0: PRO-COM 6500 Satin/Low Sheen
DCPR00-0: DECOPRIME Primer	PCFL30-0: PORCH & FLOOR Eggshell
DGLO30-0: DECOGLO Eggshell	PCHB00-0: PRO-COM High Build Primer-Surfacer
DGLO50-0: DECOGLO Semi-Gloss	PCMA00-0, -1: PRO-COM 6500 Primer
ENCT30-0: ENDURA-COAT Eggshell	PCMP00-0, -1: PRO-COM Multi-Purpose Primer
ENCT50-0: ENDURA-COAT Semi-Gloss	PMCE10-0: CONTRACTOR'S EDGE Flat
ENCT60-0: ENDURA-COAT Gloss	PMCE30-0: CONTRACTOR'S EDGE Eggshell
ENPR00-0: ENDURAPRIME Primer	PMCE50-0: CONTRACTOR'S EDGE Semi-Gloss
ENPX50-0: ENDURACAT Semi-Gloss	PRWL00-0: PREP-WALL Drywall Surface Conditioner
ESPR00-1: EFF-STOP Premium	SBPR00-0: Smooth BLOCFIL Premium
ESSL00-0: EFF-STOP Select	SBSL00-1: Smooth BLOCFIL Select
EVER10-0, -1: EVEREST Flat	SFSL00-1: SURFACO Select
EVER20-0, -1: EVEREST Velvet	SLPR00-2: SUPER-LOC Premium
EVER30-0, -1: EVEREST Eggshell	Continued...

SDS FORM A: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS continued...

SPMA10-1: SUPREMA Flat
SPMA20-1: SUPREMA Velvet
SPMA30-0: SUPREMA Eggshell
SPMA40-1: SUPREMA Satin/Low Sheen
SPMA50-0, -1: SUPREMA Semi-Gloss
SSHL10-0: SPARTASHIELD Flat
SSHL20-0: SPARTASHIELD Velvet
SSHL30-0: SPARTASHIELD Eggshell
SSHL40-0: SPARTASHIELD Satin/Low Sheen
SSHL50-1: SPARTASHIELD Semi-Gloss
SSHL60-1: SPARTASHIELD Gloss
SSHV10-0: SPARTASHIELD VA Flat
SWLL10-0: SPARTAWALL Flat
SWLL20-1: SPARTAWALL Velvet
SWLL30-1: SPARTAWALL Eggshell
SWLL40-1: SPARTAWALL Satin/Low Sheen
SWLL50-1: SPARTAWALL Semi-Gloss
SWLR10-0: SUPER-WALL Flat Ready-To-Use
SZRO10-0: SPARTAZERO Flat
UGPR00-1: ULTRA-GRIP Premium
UGSL00-1: ULTRA-GRIP Select Zero VOC
ULGM00-0: ULTRASHIELD Galvanized Metal Primer
ULSB10-0: ULTRA-SCRUB Flat
VNPL00-0: VINYLASTIC Plus
VNPR00-1: VINLYLASTIC Premium Ultra-Low VOC
VNSL00-1: VINYLASTIC Select Zero VOC
W 360V: ENDURASEAL Primer
W 5361: Athletic Field Striping Paint
W 6139: Acrylic Elastomeric Coating AZ
W 6160E: VERSAGLO
W 6220E: VERSAGLOSS
W 6230E: VERSAWALL
W 6240: VERSAFLAT
W 6250E: VERSASATIN

SAFETY DATA SHEET

FORM A: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS

SDS DATE: 01/25/2025

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTIFICATION:
SEE COVER PAGE FOR LIST OF PRODUCTS COVERED

MANUFACTURER: DUNN-EDWARDS CORPORATION
6119 E. WASHINGTON BLVD
COMMERCE, CA 90040

PRODUCT TYPE: WATERBORNE PAINT
RECOMMENDED USE: ARCHITECTURAL COATING

EMERGENCY PHONE: 1-800-222-1222
OTHER CALLS: (213) 431-4925

HMIS CODES: H F R PP
0 0 0 E



SECTION 2: HAZARDS IDENTIFICATION

GHS CLASSIFICATION: NOT A HAZARDOUS SUBSTANCE OR MIXTURE.

GHS LABEL ELEMENTS: [NOTE: THIS CONSUMER PRODUCT IS EXEMPT FROM OSHA GHS-HCS LABELING REQUIREMENTS.]

SIGNAL WORD: (NONE REQUIRED) HAZARD STATEMENT: (NONE REQUIRED)

PICTOGRAM: (NONE REQUIRED)

PRECAUTIONARY STATEMENTS:

PREVENTION: DO NOT INGEST. USE ONLY WITH ADEQUATE VENTILATION. AVOID BREATHING VAPORS, SPRAY MIST AND SANDING DUST. WEAR APPROPRIATE NIOSH-APPROVED RESPIRATORY PROTECTION WHEN SPRAYING OR SANDING. AVOID CONTACT WITH SKIN AND EYES. CLOSE CONTAINER AFTER EACH USE. KEEP OUT OF REACH OF CHILDREN.

RESPONSE: CLEAN UP SPILLS WITH INERT ABSORBENT MATERIAL, SUCH AS CLAY GRANULES, PAPER OR CLOTH WIPES. ALLOW TO DRY BEFORE DISPOSAL.

STORAGE & DISPOSAL: KEEP BETWEEN 40°F AND 110°F AT ALL TIMES. DISPOSE OF CONTAINER AND CONTENTS IN ACCORDANCE WITH APPLICABLE LOCAL, STATE AND FEDERAL REGULATIONS.

HAZARDS NOT OTHERWISE CLASSIFIED: NONE.

SECTION 3: COMPOSITION / INFORMATION ON INGREDIENTS

SUBSTANCE OR MIXTURE: MIXTURE

HAZARDOUS INGREDIENTS:

CHEMICAL NAME	COMMON NAME / SYNONYMS	CAS NUMBER	CONCENTRATION (%WT)
---------------	------------------------	------------	---------------------

NO REPORTABLE HAZARDOUS INGREDIENTS.

NOTE: EXPOSURES TO POSSIBLE HAZARDOUS INGREDIENTS BELOW REPORTING THRESHOLDS CAN BE REDUCED OR AVOIDED BY FOLLOWING RECOMMENDED PROCEDURES FOR SAFE HANDLING, STORAGE, DISPOSAL, AND USE.

SAFETY DATA SHEET

FORM A: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS

SDS DATE: 01/25/2025

SEE SECTION 11 (TOXICOLOGICAL INFORMATION) FOR POSSIBLE HAZARDOUS BY-PRODUCTS.

SECTION 4: FIRST-AID MEASURES

EYES: FLUSH EYES WITH FRESH WATER FOR AT LEAST 15 MINUTES.

SKIN: WASH THOROUGHLY WITH SOAP AND WATER.

INGESTION: HAVE VICTIM DRINK 1 OR 2 GLASSES OF WATER TO ENSURE DILUTION.

INHALATION: MOVE VICTIM TO FRESH AIR.

MOST IMPORTANT SYMPTOMS AND EFFECTS: MAY CAUSE MILD IRRITATION TO SKIN AND EYES, GASTROINTESTINAL AND RESPIRATORY TRACTS. SLIGHT DIZZINESS, NAUSEA AND HEADACHE POSSIBLE.

NOTES TO FIRST AID PROVIDERS: CALL FOR MEDICAL ASSISTANCE IF SYMPTOMS PERSIST.

SECTION 5: FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: FOAM, ALCOHOL FOAM, CO2, DRY CHEMICAL, WATER FOG.

UNUSUAL FIRE AND EXPLOSION HAZARDS: LIQUID MATERIAL IS NON-COMBUSTIBLE, BUT DRIED FILMS ARE CAPABLE OF SUPPORTING COMBUSTION WHEN IN CONTACT WITH OPEN FLAMES. CLOSED CONTAINERS CAN DEVELOP INTERNAL PRESSURE AND MAY RUPTURE WHEN SUBJECTED TO EXTREME HEAT.

HAZARDOUS COMBUSTION PRODUCTS: COMBUSTION CAN PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE.

SPECIAL EQUIPMENT & PRECAUTIONS: USE SELF-CONTAINED BREATHING APPARATUS IN CONFINED SPACES. OBSERVE RECOMMENDED PROCEDURES FOR HANDLING ORDINARY COMBUSTIBLE MATERIALS.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, EMERGENCY PROCEDURES: WEAR WATERPROOF GLOVES TO AVOID SKIN CONTACT. KEEP CHILDREN AND PETS AWAY FROM SPILLED LIQUID. PREVENT LIQUID FROM ENTERING DRAINS, WATERWAYS, AND SOIL. AVOID EATING OR DRINKING WHEN HANDLING AND WASH HANDS AFTER USE BEFORE DOING SO.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEAN UP: DIKE SPILLED LIQUID WITH INERT MATERIAL, SUCH AS CLAY GRANULES. SCOOP UP EXCESS LIQUID AND POUR INTO CONTAINER. USE PAPER OR CLOTH WIPES TO CLEAN UP SMALL SPILLS. ALLOW TO DRY BEFORE DISPOSAL.

SECTION 7: HANDLING AND STORAGE

SAFE HANDLING PRECAUTIONS: KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT STACK CONTAINERS MORE THAN THREE HIGH. SECURE LOADS AGAINST SHIFTING DURING TRANSPORTATION. USE ONLY AN APPROPRIATE TOOL TO OPEN CONTAINERS.

SAFE STORAGE CONDITIONS: STORE IN COOL, WELL-VENTILATED AREA. MAINTAIN TEMPERATURE BETWEEN 40°F AND 110°F. AVOID EXPOSURE TO DIRECT SUNLIGHT, HEAT OR FLAME. INSPECT CONTAINERS FOR LEAKS PERIODICALLY. ROTATE STOCK, USE OLDER MATERIAL FIRST.

INCOMPATIBILITIES: DO NOT HANDLE OR STORE NEAR WATER-REACTIVE MATERIALS, STRONG OXIDIZERS, ACIDS OR ALKALIS.

SAFETY DATA SHEET

FORM A: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS

SDS DATE: 01/25/2025

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

HAZARDOUS INGREDIENTS	CAS NUMBER	%WT	ACGIH TLV/TWA PPM	OSHA EXPOSURE LIMITS				VAPOR PRESS mmHg @ TEMP
				TWA PPM	MG/M ³	STEL PPM	MG/M ³	

NO REPORTABLE HAZARDOUS INGREDIENTS.

ENGINEERING CONTROLS:	USE SIGNS OR BARRIERS TO RESTRICT ACCESS TO PAINTING WORK AREA.
VENTILATION :	NORMAL AIR CIRCULATION SHOULD BE SUFFICIENT; OTHERWISE, USE PORTABLE FANS. ENSURE ADEQUATE VENTILATION DURING APPLICATION, DRYING AND CURING OF PAINT.
RESPIRATORY PROTECTION:	FOR SPRAY APPLICATION, USE A NIOSH-APPROVED PARTICULATE FILTER MASK (RATED N100 OR HIGHER) TO AVOID BREATHING SPRAY MIST. EXPOSED PERSONS WITH ALLERGIES OR ASTHMA MAY NEED AN ORGANIC VAPOR/PARTICULATE RESPIRATOR (NIOSH/MSHA TC 23C OR EQUIVALENT). WHEN SANDING, SCRAPING, OR ENGAGING IN ANY ACTIVITY THAT GENERATES AIRBORNE NUISANCE DUST, WEAR A NIOSH-APPROVED PARTICULATE FILTER MASK (RATED N100 OR HIGHER) TO AVOID BREATHING DUST. FINISH CLEANUP BY WATER-WASHING ALL SURFACES TO REMOVE DUST RESIDUE.
EYE PROTECTION:	USE SAFETY GLASSES, GOGGLES, OR FACE SHIELD TO PROTECT EYES.
SKIN PROTECTION:	USE WATERPROOF GLOVES (LATEX, VINYL, RUBBER, OR NEOPRENE) TO AVOID SKIN CONTACT. WASH OFF ANY PAINT FROM SKIN WITH SOAP AND WATER.
OTHER PROTECTIVE CLOTHING OR EQUIPMENT:	WATERPROOF HEADCOVERING AND GENERAL PROTECTIVE CLOTHING ARE RECOMMENDED FOR PROTECTION AS NECESSARY.
WORK HYGIENIC PRACTICES:	WASH HANDS AND FACE WITH SOAP AND WATER BEFORE EATING OR DRINKING.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	OPAQUE LIQUID DISPERSION	VAPOR PRESSURE:	SAME AS WATER VAPOR	
ODOR:	VERY MILD ODOR	VAPOR DENSITY:	SAME AS WATER VAPOR	
ODOR THRESHOLD:	(NO INFORMATION AVAILABLE)	SPECIFIC GRAVITY:	~1.4 (H ₂ O = 1)	
pH AS SUPPLIED:	~8.5	SOLUBILITY IN WATER:	PARTLY SOLUBLE	
FREEZING POINT:	0° C / 32° F	PARTITION COEFFICIENT:	(NO INFORMATION AVAILABLE)	
BOILING POINT:	100° C / 212° F	AUTO-IGNITION TEMP:	(NOT APPLICABLE)	
FLASH POINT:	(NOT APPLICABLE)	DECOMPOSITION TEMP:	(NO INFORMATION AVAILABLE)	
EVAPORATION RATE:	SAME AS WATER	VISCOSITY:	85 – 115 KU	
FLAMMABILITY:	(NOT APPLICABLE)	PERCENT SOLIDS:	BY VOL: ~35%	BY WT: ~50%
UPPER EXPLOSIVE LIMIT:	(NOT APPLICABLE)	PERCENT VOLATILE:	BY VOL: ~65%	BY WT: ~50%
LOWER EXPLOSIVE LIMIT:	(NOT APPLICABLE)			

SAFETY DATA SHEET

FORM A: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS

SDS DATE: 01/25/2025

SECTION 10: STABILITY AND REACTIVITY

REACTIVITY: REACTIVITY NOT KNOWN TO OCCUR UNDER NORMAL CONDITIONS.

CHEMICAL STABILITY: STABLE UNDER NORMAL CONDITIONS.

POSSIBILITY OF HAZARDOUS REACTIONS: POLYMERIZATION WILL NOT OCCUR.

CONDITIONS TO AVOID: AVOID STORAGE AT TEMPERATURES ABOVE 110° F. SEE PRODUCT PDS FOR LOW TEMPERATURE STORAGE CONDITIONS.

INCOMPATIBLE MATERIALS: AVOID WATER-REACTIVE MATERIALS, STRONG OXIDIZERS, ACIDS AND ALKALIS.

HAZARDOUS DECOMPOSITION PRODUCTS: COMBUSTION CAN PRODUCE CARBON MONOXIDE AND/OR CARBON DIOXIDE.

SECTION 11: TOXICOLOGICAL INFORMATION

LIKELY ROUTES OF EXPOSURE: INHALATION, INGESTION, EYE AND SKIN CONTACT

SYMPTOMS OF OVEREXPOSURE: MAY CAUSE MILD IRRITATION TO SKIN AND EYES, GASTROINTESTINAL AND RESPIRATORY TRACTS. SLIGHT DIZZINESS, NAUSEA AND HEADACHE POSSIBLE.

DELAYED OR CHRONIC EFFECTS: AVAILABLE INFORMATION PROVIDES NO EVIDENCE OF DELAYED OR CHRONIC HEALTH EFFECTS ASSOCIATED WITH EXPOSURE TO THIS PRODUCT DURING NORMAL USE WITH RECOMMENDED PERSONAL PROTECTION AS NEEDED.

NUMERICAL MEASURES OF TOXICITY: (NO INFORMATION AVAILABLE)

CARCINOGENICITY (WHOLE PRODUCT): ACGIH? NO. IARC? NO. NIOSH? NO. NTP? NO. OSHA? NO.

HAZARDOUS BY-PRODUCTS: SPRAY APPLICATION OF THIS PRODUCT CAN GENERATE SPRAY MIST, WHICH MAY BE HARMFUL IF INHALED. RESPIRATORY IRRITATION AND SHORTNESS OF BREATH POSSIBLE. RISK DEPENDS ON LEVEL AND DURATION OF EXPOSURE.

SANDING, SCRAPING, OR OTHERWISE DISTURBING THE DRY FILM OF THIS PRODUCT CAN GENERATE AIRBORNE NUISANCE DUST, WHICH MAY BE HARMFUL IF INHALED. RESPIRATORY IRRITATION AND SHORTNESS OF BREATH POSSIBLE. RISK DEPENDS ON LEVEL AND DURATION OF EXPOSURE.

SEE SECTION 8 (EXPOSURE CONTROLS / PERSONAL PROTECTION) FOR INFORMATION ON RESPIRATORY PROTECTION WHEN SPRAYING OR SANDING.

NOTE: SPRAY MIST OR SANDING DUST MAY CONTAIN TITANIUM DIOXIDE PIGMENT PARTICLES BOUND IN THE RESINOUS MATRIX OF (1) PAINT DROPLETS THAT MAKE UP SPRAY MIST OR (2) PAINT FRAGMENTS THAT MAKE UP SANDING DUST. TITANIUM DIOXIDE, IN THE FORM OF AIRBORNE, UNBOUND PARTICLES OF RESPIRABLE SIZE, HAS BEEN CLASSIFIED BY IARC AS GROUP 2B: POSSIBLY CARCINOGENIC TO HUMANS, BASED ON TWO LABORATORY WHITE RAT INHALATION EXPOSURE STUDIES, IN WHICH LUNG OVERLOAD CONDITIONS RESULTED IN TUMOR FORMATION. THE IARC MONOGRAPH ON TITANIUM DIOXIDE, HOWEVER, STATES AT THE CONCLUSION OF ITS SUMMARY CHAPTER: "NO SIGNIFICANT EXPOSURE TO PRIMARY PARTICLES OF TITANIUM DIOXIDE IS THOUGHT TO OCCUR DURING THE USE OF PRODUCTS IN WHICH TITANIUM DIOXIDE IS BOUND TO OTHER MATERIALS, SUCH AS IN PAINTS." ALSO, MULTIPLE EPIDEMIOLOGICAL STUDIES OF TITANIUM DIOXIDE PRODUCTION WORKERS WITH LONG-TERM OCCUPATIONAL EXPOSURE TO AIRBORNE TITANIUM DIOXIDE DUST FOUND NO RELIABLE CORRELATION BETWEEN EXPOSURE AND INCIDENCE OF LUNG CANCER OR OTHER CHRONIC LUNG DISEASES. SCIENTISTS AT MAJOR SUPPLIERS OF TITANIUM DIOXIDE PIGMENT TO DUNN-EDWARDS HAVE EACH PERFORMED AN INDEPENDENT GHS HAZARD CLASSIFICATION OF TITANIUM DIOXIDE PIGMENT AND EACH CONCLUDED THAT TITANIUM DIOXIDE PIGMENT IS "NOT A HAZARDOUS SUBSTANCE OR MIXTURE," BASED ON THE WEIGHT OF SCIENTIFIC EVIDENCE.

SPRAY MIST OR SANDING DUST MAY ALSO CONTAIN QUARTZ AND/OR CRISTOBALITE PARTICLES BOUND IN THE RESINOUS MATRIX OF (1) PAINT DROPLETS THAT MAKE UP SPRAY MIST OR (2) PAINT FRAGMENTS THAT MAKE UP SANDING DUST. QUARTZ AND CRISTOBALITE ARE TWO VARIETIES OF CRYSTALLINE SILICA, WHICH, IN THE FORM OF AIRBORNE, UNBOUND ("FREE") PARTICLES OF RESPIRABLE SIZE, HAS BEEN CLASSIFIED BY IARC AS GROUP 1: CARCINOGENIC TO HUMANS, BASED ON EVIDENCE THAT LONG-TERM OCCUPATIONAL EXPOSURE TO FREE CRYSTALLINE SILICA DUST CAN CAUSE SILICOSIS, A CHRONIC LUNG DISEASE THAT MAY PROGRESS TO LUNG CANCER. EXPOSURE TO FREE CRYSTALLINE SILICA DUST COMMONLY OCCURS IN WORK WITH ROCK, STONE, GRAVEL, SAND, SOIL, CONCRETE, AND MASONRY.

SAFETY DATA SHEET

FORM A: COATINGS WITH NO REPORTABLE HAZARDOUS INGREDIENTS

SDS DATE: 01/25/2025

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: (NO INFORMATION AVAILABLE)

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: COLLECT SPILLED MATERIAL, USED ABSORBENT MATERIAL AND WIPES INTO A SUITABLE CONTAINER AND DISPOSE IN ACCORDANCE WITH ALL APPLICABLE LOCAL, STATE, AND FEDERAL REGULATIONS. DRY, EMPTY CONTAINERS MAY BE RECYCLED OR DISPOSED OF AS ORDINARY TRASH.

RCRA HAZARD CLASS: NON-HAZARDOUS

SECTION 14: TRANSPORT INFORMATION

THIS MATERIAL IS NOT SUBJECT TO DOT, IATA/ICAO, OR IMO/IMDG TRANSPORTATION REGULATIONS. ACCEPTABLE FOR AIR TRANSPORT AS NON-HAZARDOUS GOODS.

UN NUMBER: (NOT APPLICABLE) UN PROPER SHIPPING NAME: (NOT APPLICABLE)

TRANSPORT HAZARD CLASS: (NOT APPLICABLE) PACKING GROUP: (NOT APPLICABLE)

ENVIRONMENTAL HAZARDS: (NOT APPLICABLE) TRANSPORT IN BULK: (NOT APPLICABLE)

SPECIAL PRECAUTIONS: FOLLOW RECOMMENDED PROCEDURES FOR SAFE HANDLING AND STORAGE.

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS:

TSCA: ALL COMPONENTS ARE LISTED IN TSCA INVENTORY OR EXEMPT.

CERCLA: NOT LISTED AS A HAZARDOUS SUBSTANCE.

SARA TITLE III: NOT LISTED AS A HAZARDOUS SUBSTANCE.

311/312 HAZARD CATEGORIES: (NOT APPLICABLE)

313 REPORTABLE INGREDIENTS: (NOT APPLICABLE)

STATE REGULATIONS: CALIFORNIA PROPOSITION 65 NOTICE:

 **WARNING:** CANCER AND REPRODUCTIVE HARM – WWW.P65WARNINGS.CA.GOV

SECTION 16: OTHER INFORMATION

DATE OF PREPARATION: JANUARY 24, 2025

PREPARER INFORMATION: DUNN-EDWARDS CORPORATION
ENVIRONMENTAL AFFAIRS DEPARTMENT
EMAIL: ENVIRONMENTAL@DUNNEDWARDS.COM

DISCLAIMER: THE INFORMATION CONVEYED ABOVE, ALTHOUGH OBTAINED FROM SOURCES WE CONSIDER RELIABLE, IS FURNISHED BY DUNN-EDWARDS CORPORATION WITHOUT ANY WARRANTY (WHETHER EXPRESS OR IMPLIED) AS TO ITS ACCURACY, ADEQUACY, OR APPLICABILITY TO ANY PARTICULAR NEEDS OR CIRCUMSTANCES.